


## ELECTRICAL PEDESTRIAN SWING-GATE

Model: Ww-883

Ww-883D (Double-gate)





# **Principle**

An optical sensors controlled passageway with bars to prevent unauthorized passage

provides excellent access control. Designed to be in sight of reception staff, the Argus takes the problem out of checking individual passes whilst allowing authorized persons to pass unhindered. The unit is at its optimum when used in conjunction with a hands free access system in which allows the bars to stay in the opening position until an unauthorized person is detected.

### **Finish**

- · Steel, painted according to RAL
- · Tough temper glass
- · Stainless steel, satin finish

Other models on request

#### **Door Bars**

- Normal height, rectangular / tubular shape
- Extra height, rectangular

Customised design by agreement

### Reader interface

Compatible with access control systems standards

- · serial interfaces
- fieldbus cross linkage

Special interfaces, signal exchange with building services automation and connection of customer supplied control elements available on request.

Export variants on request

# **Operation**

The door bars open and close automatically.

Adjustable modes of operation are:

· open ground state

The door leaves are being closed automatically as soon as an unauthorized passage is registered.

closed ground state

The door bars are being opened / closed automatically in respect to passage direction and then closed / open again.

## **Entry direction**

- · clear
- locked
- electrically controlled
- by an access control system
- manual

### **Exit direction**

- · clear
- locked
- electrically controlled
- by an access control system
- manual

## **Construction**

Casing and guiding tube sheets of high-quality.

Glazing: 10 mm toughened glass

# **Electrical Equipment**

Control integrated in the unit supply: 230 V AC 50 Hz

## **Options**

- Installation of card readers
- Signal equipment
- Control desk or panel for remote control (release & block)
- Mode selection switch
- · Railing elements for flow guidance or as barrier in a suitable design
- · Counting mechanism

